

# **STANDALONE CLOUD** APPLICATION BASED CAMERA

Soho Sky Full hd pan-tilt outdoor camera





Cloud Storage	ດີນີ້ IoT	Color View at Night	Auto Tracking	Two Way Audio	Movable Camera	IP 65 Weather Proof	
------------------	--------------	---------------------	------------------	------------------	-------------------	------------------------	--

2MP full HD (1920 x 1080) in	mage resolution camera
------------------------------	------------------------

Color View at night with Spot Light

Moveable camera from phone(Pan and Tilt)

Smart Al Human Auto-tracking

Intelligent Motion/Sound detection

Cloud Storage/Support SD card (max. 128GB)

Two-way audio

Intelligent motion detection available with zones selection

IP65 Weather Proof Outdoor Enclosure

### **TECHNICAL SPECIFICATIONS**

## SoHo Sky

Camera	Image Sensor	1/2.9" 2 Megapixel Progressive Scan CMOS Sensor	
	Signal System	PAL/NTSC	
	Effective Pixels	1920 (H) × 1080 (V)	
	Minimum Illumination	Color :0.1 lux@F2.0, Black/White: 0.01 lux@F2.0	
	Electronic Shutter Speed	1/20~1/10,000s	
	Pan/Tilt	Pan: 0~350°, Tilt: -90°~30°	
Lens	Lens Type	3.0 mm	
	FOV	102°/54°/130°	
Day/Night Functionality	Day & Night	Auto(ICR)/Color/B&W	
	Night Vision Distance	Up to 10m	
	Video Compression	H.264	
Compression	H.264 Codec Profile	Main profile	
	Video Bit Rate	32 Kbps ~ 2Mbps	
Resolution and Frame Rate	Max. Resolution	1920×1080	
	Frame Rate	1~25fps	
	Wide Dynamic Range (WDR)	DWDR	
Operational	Codec Streaming Capability	Dual streaming	
Features	Storage	Built-in micro SD card(Max.128GB), cloud storage, NVR	
	Alarm Trigger	Intelligent motion detection	
	Protocols	HTTP, DHCP, DNS, TCP/IP, RTSP	
	Interface Protocol	Private	
	Wireless	2.4G WIFI (IEEE802.11b/g/n)	
	Wireless Security	64/128-bit WPA/WPA2, WPA-PSK/WPA2-PSK, WPS	
Network & Interface	Mobile Client Application	Supports iOS 9 or later, Android 5 or later	
	Max.User Access	6	
	Security	AES128	
	Audio Input/Output	Built-in mic/speaker	
	Power Supply	DC 12V/1A	
General	Power Consumption	Max. 4.5W	
	IP Rating	IP65	
	Operating Temperature	-20 °C to 50 °C	
	Optional Accessory	Solar panel	
	Dimensions	148 × 103 × 108mm	
	Net Weight	530g	

\*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

\*\*Cameras will connect only with 2.4GHz WiFi connection

### VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED.

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton West Midlands, WV6 0JZ United Kingdom Ph:+44-1902-793383, Email: sales@vantagesecurity.com www.vantagesecurity.com

#### (AN ISO 9001 : 2008, ISO 14001:2004 CERTIFIED COMPANY)

