



VP-3010JK-IP3AX1

4 AXIS JOYSTICK KEYBOARD CONTROLLER



FEATURES

Multi functional Joystick Keyboard for controlling PTZ camera

4-Axis joystick control PTZ functions

Digital Keyboard with LCD screen

Supports 16 users accounts: 1 admin and 15 operators

Supports communication via network , USB and serial interface

TECHNICAL SPECIFICATIONS

VP-3010JK-IP3AX1

Parameter	Specifications
Keyboard Key Panel	Electromechanical
Joystick	Four-axis Vector-solving Twisting Function Return to Center
Display	Built-in LCD screen 128 x 64 pixel
Operation Support	Pan, tilt, zoom control, image capture
Control Mode Support	Network, RS-232, RS-422 and RS-485
Keyboard Connection Interface	Serial interface: RS-232, RS-422, RS-485 USB interface: 3.0 USB Network interface: RJ45 (10M/100M/1000M self-adaptive Ethernet)
Plug & Play Integration	Proprietary protocol supports auto configuration of device for full compatibility of live view, playback and recording retrieval remotely in video management software.
System Compatibility	Onvif supported
Power Supply	DC 12V
Power Consumption	≤ 3W
Working Temperature	-35°C to +72° C
Working Humidity	95% or less non condensing
Dimensions (W × H × D)	435 × 110 × 193 mm
Net Weight	≤1 kg
Certifications	CE, FCC, RoHS

^{*}Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image, weights and measurements are approximate and may vary due to customized solutions & products being offered as per customer requirements.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton West Midlands, WV6 0JZ United Kingdom Ph:+44-1902793383, Email: sales@vantagesecurity.com





(AN ISO 9001: 2008, ISO14001: 2004 CERTIFIED COMPANY)

