

IP VIDEO DOOR PHONE SYSTEM

VP-CS72GS-IPV2 GUARD MANAGEMENT UNIT



FEATURES

Protocol: Standard TCP/IP

10.1 inch capacitive touch screen with advanced GUI

Card management function for ID card registration

Supports SOS master reset for opening all apartment doors in case of emergency

Alarm management function

Supports IP CCTV cameras

Supports Intercom function

Communication with Management software for master programming



Camera
Interface



10.1" Color LCD
Display



Two way audio



ID Card



TCP/IP

TECHNICAL SPECIFICATIONS

VP-CS72GS-IPV2

Parameter	Specifications
Display	10.1" TFT LCD
Camera Pixels	2MP CMOS camera
Display Resolution	1280x800
Display Type	Capacitive touch screen
Touch Screen	Yes
Ring Duration	30s
Call Duration	120s
Monitor Duration	30s
Power supply	DC 24V
Static Current	≤ 100mA
Working Current	≤ 300mA
Temperature	-10°C - +55°C
Humidity	20%-93%
Dimension (W/H/D)	210×356×31.8 mm
Certifications	CE, FCC, ROHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image, weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph: +44-1902-793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO 14001:2004 CERTIFIED COMPANY)

