

IP VIDEO DOOR PHONE SYSTEM

VP-CS91TS-IPV2 Outdoor Tower Calling Station



 Safe Homes.
Safe Communities.

FEATURES

- 1.3 MP CMOS color camera
- Display: 4.3inch LCD with advanced GUI
- Working voltage: DC 24V (support POE)
- Call indoor monitor
- Support password/IC or ID card for unlocking
- Support Intercommunication function
- TCP/IP Digital System
- Inbuilt microphone and speaker set
- Support tamper alarm



IR LEDs



Speaker



High
Resolution
Camera



TCP/IP



Microphone

TECHNICAL SPECIFICATIONS

VP-CS91TS-IPV2

| Parameter | Specifications |
|---------------------------|------------------|
| Working Voltage | DC24V/POE |
| Working Current | ≤210 mA |
| Static Current | ≤100 mA |
| Camera | 1.3MP CMOS Color |
| View Angle | Diagonal 110° |
| Minimum Illumination | 0 lux |
| IR Night Vision | Yes |
| Storage Temperature | -40°C ~ 70°C |
| Environmental Temperature | -25°C - +70°C |
| Ring Duration | 30 Second |
| Call Duration | 120 Second |
| Monitor Duration | 30 Second |
| Dimension (W/H/D) | 148x363x47 mm |
| Certifications | CE, FCC, ROHS |

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image, weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902-793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO 14001:2004 CERTIFIED COMPANY)

