

WALK THROUGH METAL DETECTOR

VP-MD33Z43-NDFWZ6 WATERPROOF DOOR FRAME METAL DETECTOR



FEATURES

33 Zones walk through metal detector door with uniform screening

Anti-interference digital filtering technology adapted by signal processor

Ultra-fast detection with a throughput rate of up to 40 person per minute

Buzzer and LED array for audio-visual alarms

Integrated programming panel with real-time traffic counter display

IP65 rated robust shockproof design suitable for diverse installation scenarios



33
Zones



Digital
Counter



Audio Visual
Alarm



IP65
Water Proof

TECHNICAL SPECIFICATIONS

VP-MD33Z43-NDFWZ6

Parameter	Specifications
Detection Zones	33 Zones
Sensitivity	0 to 400 level each zones
Detection	Uniform from top to bottom without blind spots in all zones with pin-point detection for large, medium and small metal objects
Alarm	Audio alarm along with LED indication on detection of Ferrous, Non-Ferrous, Metal and Alloy
Zone Indicator	LED array on the detector panel
Display	Digital display integrated with programming keypad
Traffic Counter	Counts number of passers by and alarms - 'IN', 'OUT', 'NET' and 'ALARM'
Throughput Rate	≥ 40 person per minute (depending upon queue management)
Traffic Flow Indicator	Supports red and green LED to assist in the smooth flow of people through the passage
Auxiliary Gates Integration	Restricts opening of tripod turnstile, flap barrier, swing gates and door locks etc. in case metal alarm is triggered.
Application Environment	Selectable upto 60 different application scenarios to automatically adapt sensitivity
Operating Frequency	0-99 operating frequency sets. The operating frequency shall be selected to make it noise free frequency band
User Access Rights	The unit shall have fully configurable user access rights, enabling different types of users to have access to all or only some specific functions
Security Level	1 to 100
Configurable User Levels	Supported with 1 level passcode
Access Code Protection	Parameters adjustments are access code protected
Dual Password Protection	Supported
Interference Suppression	Digital filtering by signal processor
Stand-by Mode	Supports infrared technology to automatic start-stop
Self Diagnostic and Calibration	Power on initiates system diagnosis and self-calibration
Equipment Protection	Robust structure for safeguarding electronic unit
Cable Management	Aviation plug for secured connection
Battery life	4 hours (optional) 8 hours (optional)
Operating Voltage	AC100V~240V 50/60Hz
Working Environment	-20°C~65°C
Working Power	12W
Working Humidity	95%, no condensation
IP Rating	IP65 waterproof
Vertical Overall Dimension	2214x886x536 (mm)
Vertical Dimensions of Passage	2011x720x536 (mm)
Net Weight	43 Kgs
Installation Environment	100cm wide x 200cm long (minimum range without metal)

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO14001 : 2004 CERTIFIED COMPANY)

