




PEOPLE ENTRANCE MANAGEMENT SYSTEM

VP-PM5020SC/DC-SGT3 SINGLE / DOUBLE CORE SLIDING GATE







FEATURES

Heavy-duty motorized-automatic slide gate

Single/dual machine core with bi-directional operating modes supported

CE FC RoHS

Half height operation with standard passage width 600mm

LED status indicator & adjustable time out delay

Automatic reset of barrier gate after each passage

Integration support with any RFID/Biometric Reader through NO input

Fail safe function supported in case of emergency

Top quality AISI 304 grade SS construction


www.vantagesecurity.com


VP-PM5020SC/DC-SGT3


| Parameter | Specifications |
|-------------------------|---|
| Passage Width | Standard 600mm; optional 900 mm |
| Throughput Rate | 35-40 persons per minute |
| Opening & Closing Speed | 0.5 ~ 0.8s |
| Passing Time | 5s default (adjustable 0-25s) |
| Safety Sensors | 9 pairs of infrared sensors for smooth passage traffic and protection of pedestrian |
| Passage Direction | Unidirectional/ bidirectional |
| Drive | Electro-mechanical DC motor drive |
| Power/Mechanism Failure | Fail safe status for either one or both directions be in free movement mode |
| Fire Alarm Integration | Supported to provide free passage for evacuation |
| Motor Power | 100W (DC brushless Servo motor) |
| Service Life | >10 million operation cycles |
| Communication Interface | Relay Input (NO/NC/COMM) Optional RS232/RS485 |
| Operating Voltage | DC 24V |
| Power Supply Voltage | AC100~240 V |
| Max. Power Consumption | 150W |
| IP Rating | IP44 |
| Working Temperature | -25°C~+70°C |
| Relative Humidity | ≤90% no condensation |
| Chassis Material | Top quality AISI 304 grade stainless steel (optional 316 grade) |
| Door Material | Tempered glass flaps |
| Dimension | 1500x300x980mm |
| Net weight | 140kg single core, 180kg double core |
| Certifications | CE, FCC, ROHS |

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image & weights, measurements are approximate and may vary.

DIMENSIONS










TECHNICAL SPECIFICATIONS

VP-PM5020SC/DC-SGT3

INSTALLATION DIAGRAM







VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED.

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton West Midlands, WV6 0JZ United Kingdom Ph:+44-1902-793383, Email: sales@vantagesecurity.com www.vantagesecurity.com (AN ISO 9001 : 2008, ISO 14001:2004 CERTIFIED COMPANY)

