

ACCESS CONTROL ACCESSORIES

VV-AX1201EM-DDC4

DOUBLE DOOR EM LOCK 1200 LBS WITH DOOR STATUS
FEEDBACK



FEATURES

Double door electro-magnetic lock with 1200 Lbs holding force

Surface mount

With dual color LED indication

Operating voltage 12VDC

Current drawn 500mA

Operating Temperature -10°C-55°C

Integration support with any access control system through NO/ NC input

VV-AX1201EM-DDC4

Parameter	Specifications
Construction	Durable aluminum, special anti-residual magnetism design for safer access control automation
Service Life	More than 1 million operations
Holding Force	1200 lbs for Double Door locks
Connection Interface	5 wire
Audio Visual Alarm	Built-in LED & buzzer
Lock Signal	Supported
Voltage	Supported
Time Delay	Supported
Push Function	Supported
Door Status	Supported
Voltage	DC 12V 450mA or DC 24V 200mA
Power Supply	DC 12V 1A
Accessories	Optional brackets: Z, L & U type
Operating Temperature	-35° C to 75° C
Dimension	500(L) x 47(W) x 26(H) mm
Weight	3.5kg
Certifications	CE, FCC, ROHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image, weights and measurements are approximate and may vary due to customized solutions & products being offered as per customer requirements.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph: +44-1902793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO14001 : 2004 CERTIFIED COMPANY)

