

# ACCESS CONTROL ACCESSORIES

## VV-AX601EM-SDC4

SINGLE DOOR EM LOCK 600 LBS WITH DOOR STATUS  
FEEDBACK



### FEATURES

Single Door Electro-magnetic Lock with 600 Lbs holding force

Surface mount

Built-in LED indicator

Operating voltage 12VDC

Current drawn 450mA

MOV surge protection

Optional relay circuit for door status feedback

# VV-AX601EM-SDC4

Parameter	Specifications
Holding Force	600 lbs for Single Door
Connection Interface	5 wire
Audio Visual Alarm	Built-in LED & buzzer
Lock Signal	Supported
Voltage	Supported
Time Delay	Supported
Push	Supported
Door Status	Supported
Construction	Durable aluminum, special anti-residual magnetism design for safer access control automation
Service Life	1,000,000 operations
Voltage	DC 12V 450mA or DC 24V 200mA
Power Supply	DC 12V 1A
Accessories	Optional brackets: Z, L & U type
Operating Temperature	-30° C to 70° C
Dimension	250(L) x 47(W) x 26(H) mm
Certifications	CE, FCC, ROHS

\*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image, weights and measurements are approximate and may vary due to customized solutions & products being offered as per customer requirements.

## VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph: +44-1902793383, Email: [sales@vantagesecurity.com](mailto:sales@vantagesecurity.com)

[www.vantagesecurity.com](http://www.vantagesecurity.com)

(AN ISO 9001 : 2008, ISO14001 : 2004 CERTIFIED COMPANY)

