

HIGH DEFINITION

DIGITAL VIDEO RECORDER

VV-DV4708-1ST1

8 CH Hybrid DVR



FEATURES

- High performance cloud technology DVR
- 8 CH DVR supports TVI / AHD/CVI 5MP/4MP 1080P/720P/WD1 video input
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support 1080P output, true high resolution display
- Multi-mode recording: manual / timed / motion / AI recording
- 8CH simultaneously playback
- Supports remote monitoring on Mobile Client (Android, IOS), IE and through CMS
- Pentaplex: preview, record, playback, backup and remote access
- Powerful mobile surveillance by smart phones with iOS and Android OS



TECHNICAL SPECIFICATIONS

VV-DV4708-1ST1

| | | |
|-----------------------------|--|--|
| System | Operating System | Embedded Linux Operating System |
| | Multiplex Operations | Multi-channel real-time recording, playback, network operation, USB backup |
| | User interface | 16-bit true new color graphical menu interface and mouse operation |
| Bandwidth | Incoming Bandwidth | 32Mbps |
| | Outgoing Bandwidth | 60Mbps |
| Interface | Video Input | 8-ch Composite video 1.0 Vp-p, 75 ohm |
| | Audio Input | 1-ch Line in RCA input |
| | Two-way Audio | Take up channel one audio input |
| | VGA Video Output | Resolution: VGA x 1 : 1920 x 1080 / 1280 x 1024 / 1024 x 768 |
| | HDMI Video Output | Resolution: HDMI x 1 : 1920 x 1080 / 1280 x 1024 / 1024 x 768 |
| | Audio Output | RCA x 1 (linear, 600Ω) |
| | Network | RJ45 10M/100M self-adaptive Ethernet port |
| | Multi-Screen Display | 1/4/6/8/9/13/16 |
| | RS 485 | RS 485 x 1 (half-duplex) |
| Compression | USB | USB 2.0 x 2 (in the rear panel) |
| | Video Compression | H.264/H.265 |
| | Audio Compression | G.711(U/A) |
| Resolution & Frame Rate | Bit Rate | 32Kbps ~ 4Mbps |
| | Recording | 5MP Lite/ 4MP Lite/ 1080P/ 1080P Lite/ 720P/WD1 |
| | Playback | 8 ch 1080N @ 25 fps |
| Network & Remote Monitoring | Frame Rate | PAL: 25 fps @ 1080N,720P NTSC: 30 fps @ 1080N,720P |
| | Cloud Monitoring | Supported |
| | DDNS | Dynamic and Static IP support |
| | Protocols Supported | TCP/IP, PPPoE, DHCP, DNS, DDNS, UPnP, HTTP, HTTPS, NTP, SMTP |
| | CMS | Full function CMS (Central monitoring software) |
| | Client Connection | Max. 5 users access |
| | Mobile Client Application | Supports android and iOS APP for Smart phone and tablets |
| Bandwidth Control | VBR (Automatic) and CBR (Manual) supported | |

TECHNICAL SPECIFICATIONS


WV-DV4708-1ST1

| | | |
|---------------------|-----------------------|--|
| | Playback Function | Play, pause, FF, FB, digital zoom, etc. |
| | Search Mode | Time slice / time / event / tag search/ |
| | Smart Search | Highlight colors to display the camera record in a certain period of time, different colors refer to different record events |
| | Alarm Notifications | DVR, FTP, Email notification supported |
| Recording & Storage | Recording Mode | Manual, motion, exception, smart event |
| | Storage | 1 SATA port up to 10TB |
| General | Power Supply | DC12V / 2A |
| | Power Consumption | <8W (Hard disk not included) |
| | Operating temperature | -10°C to + 50°C |
| | Working Humidity | 90% or less (non condensing) |
| | Dimensions | 255 x 222 x 42mm (W x D x H) |
| | Weight | 1.45kg (without hard disk) |
| Certifications | Certifications | CE, FCC, ROHS |

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image, weights and measurements are approximate and may vary due to customized solutions & products being offered as per customer requirements.

DIMENSIONS

Unit: mm



VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph: +44-1902793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO14001 : 2004 CERTIFIED COMPANY)

