


RFID BASED ELEVATOR CONTROL SYSTEM

VV-EC32DP-2WA1 32 FLOORS ELEVATOR CONTROLLER



FEATURES

- High performance 32bit CUP processor
- Standard 10/100M TCP/IP communication
- Big capacity flash chip,120,000 card holders, 200,00 record
- Each panel support 32 outputs, & support NO/NC & we can change NO/NC through software or jumper
- Each panel can connect a expansion panel to reach 64 outputs
- Connect an expansion panel to realize visitor function
- Each door's time zone has as many as 8 groups, and each group can choose different verification methods
- Support 16 floor direct access mode and directly reach 32 floors by using expansion panel
- Support multi verifications: card, card+PSW, PSW, double cards, free pass, first card
- Support remotely open or close door with special color indication
- Support emergency door release input to realize fire alarm linkage or elevator's normal usage if emergency
- Support 1st floor arrival signal output to activate the elevator button
- Support many kinds of events alarm output like invalid card, invalid time, door alarm, or door open overtime
- Elevator controller can connect to wiegand reader with wiegand protocol like 26, 34,36
- Support the setting of each card's valid time
- All of access control devices support Rs485, TCP/IP controller's mixing installation
- Support 3 kinds of languages, and add other language by ourselves
- Real time color to show each point's open or close status
- Support full screen event showing and show vivid pic. and support synthesized voice
- Support 2 kinds of database: MS Access & MS SQL server, the default is MS Access

TECHNICAL SPECIFICATIONS

WV-EC32DP-2WA1

Parameter	Specifications
CPU	32 bit 400MHz CPU
RAM	32M
Flash Memory	128M
Number of Floors controller	32/16 Floors
Numbers of readers supported	2
Types of readers supported	26/34-bit Wiegand and RS485 Reader
Number of Outputs	32
Card holders Capacity	12,000
Log Events Capacity	200,000
Communication	TCP/IP and RS-485
Power	12V > 3mA
Power Consumption	5W
Operating Temperature	0-60 °C
Operating Humidity	10% to 95%
Dimension	218 x 136 x 32mm
Weight	450g
Certifications	CE, FCC, ROHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED.

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph: +44-1902-793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO 14001 : 2004 CERTIFIED COMPANY)

