




FULL HIGH DEFINITION 4MP IP DOME CAMERA

VV-NC41154D-AZIR2T1 IR NIGHT VISION MOTORIZED CAMERA





H.265 COMPRESSION









FEATURES

Full High Definition 4MP (2560 x 1440) resolution

30~50m IR night view distance

Inbuilt 120dB WDR, 3D DNR, HLC, ROI & BLC functions

Support Triple streams

High performance IR Cut mechanical filter for True Day & Night vision

Inbuilt Smart Analytics Features

IP67 Weather proof outdoor enclosure

VV-NC41154D-AZIR2T1

| | Image sensor | 1/3" Progressive Scan CMOS Sensor |
|--------------------------------|----------------------------|--|
| Camera | Signal System | PAL/NTSC |
| | Effective Pixels | 2560 (H) × 1440 (V) |
| | Minimum Illumination | Color: 0.005 lux @F1.6, AGC ON; 0 lux with IR |
| | Electronic Shutter Speed | 1/2s~1/100000s |
| | Gain Control | Auto |
| | White Balance | Auto |
| | Signal to Noise | > 52 dB |
| | Iris | Fixed |
| Lens | Lens Type | 2.8~12mm@ F1.4 motorized |
| | Lens Mount | Ф14 |
| | FoV | Horizontal : 92 °~31 °; Vertical: 48 °~17.2°; Diagonal: 112 °~ 35.6 ° |
| | Focus | Motorized |
| | Angle Adjustment | Pan: 0°~360°; Tilt:0°~80°;Rotation: 0°~360° |
| | Day & Night | True Day & Night with ICR |
| Day/Night | IR Cut | High performance Mechanical IR Cut Filter with auto switch |
| Functionality | IR Source | Inbuilt High intensity Smart IR LEDs with intensity control |
| | IR Range | 30~50 Mtr. |
| Compression | Video compression | H.265 / H.264 / MJPEG |
| | H.265 codec profile | Main Profile |
| | Video Bit Rate | 64 Kbps ~ 8 Mbps |
| Resolution and Frame Rate | Max. Resolution | 2560 × 1440 |
| | Main Stream | 50Hz: 4MP/3MP/1080P/720P(1~25fps) 60Hz: 4MP/3MP/1080P/720P(1~30fps) |
| | Sub Stream | 50Hz: 720P/D1/CIF (1~25fps) 60Hz: 720P/D1/CIF (1~30fps) |
| | Third Stream | 50Hz: D1/480× 240/CIF(1~25fps) 60Hz: D1/480× 240/CIF (1~30fps) |
| | HLC | Supported |
| | Wide Dynamic Range (WDR) | 120dB |
| | Backlight Compensation | Supported |
| | Defog | Supported |
| | DNR | Inbuilt 3D DNR (Digital Noise Reduction) circuit |
| | Codec Streaming Capability | Triple streaming |
| Operational Features | Image settings | ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness NR, etc. adjustable through client software or web browser |
| | General function | Watermark, IP address filtering, video mask, heartbeat, password protection, image distortion correction, etc. |
| | Onboard Storage | Built-in Micro SD / SDHC / SDXC card slot, up to 256 GB |
| | ROI | Each ROI to be configured separately |
| | Alarm Trigger | Motion detection; SD card error; SD card full |
| Network & Remote Monitoring | Protocols | UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, ICMP, IGMP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, 802.1x, UPnP, HTTPs, QoS |
| | System compatibility | ONVIF |
| | CMS | Full function CMS (Central monitoring software) |
| | Mobile Client Application | Supports android and iOS APP for Smart phone and tablets |
| | Bandwidth control | VBR (Automatic) and CBR (Manual) supported |
| | Web Browser | IE (plug-in required)/Google Chrome/Edge/Firefox/Safari |
| Analytics Feature | Smart Features | Video Exception (scene change, video blur and video cast detection), line crossing detection and region intrusion detection |
| Interface | Ethernet | 1 RJ45 10/100 Ethernet port |
| | Power Input | Standard DC Jack |
| | Audio Input | 1CH built-in MIC; 1CH audio input |
| | Reset | Yes, supported |
| | | |


VV-NC41154D-AZIR2T1


| Electrical | Power Requirement | DC12V, PoE (IEEE802.3af) |
|----------------|-----------------------|---|
| | Power Consumption | Max. 8W |
| Environmental | Enclosure | IP67 Weather proof outdoor enclosure |
| | Mounting bracket | Integrated mounting bracket with cable management |
| | Operating Temperature | -30°C to + 60°C |
| | Operating Humidity | 95% or less (non-condensing) |
| Mechanical | Color | White |
| | Dimensions | Φ 111.5 × 99.6 |
| | Weight | Approx. 0.65KG |
| Certifications | Certifications | CE, FCC, RoHS |

^{*}Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image, weights and measurements are

DIMENSIONS

Unit: mm





VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902793383, Email: sales@vantagesecurity.com



(AN ISO 9001: 2008, ISO14001: 2004 CERTIFIED COMPANY)

