

HIGH DEFINITION SMART CAMERA

VV-NC700P2P-F3 IR NIGHT VISION WIFI PAN-TILT CAMERA



FEATURES

1080P HD Video Technology

Smart IR with Intensity Control for True & Day Night Vision

Support two-way audio, with telecommunication level of signal processing

Support digital zooming

Support Cloud storage, micro SD card slot (max 128GB)

Plug & Play; Easy Mobile Device Binding Technology

Support Android/iOS system mobile device, remote real-time monitoring



Pan Tilt Control



P2P



TF Card



Night Vision



WiFi

TECHNICAL SPECIFICATIONS

VV-NC700P2P-F3

Video	Image Sensor	1/2.7" Color CMOS Sensor
	Image Resolution	1080P HD images, resolution up to 1920x1080
	Video Resolution	1080P(1920x 1080)
	Frame Rate	Max 30fps
	Min. Illumination	Color: 0.01 Lux @F1.4
	IR Source	1 Dot Matrix Infrared
	IR Distance	Up to 10 Mtr
	IR Cut	Dual IR cut filter with auto switch
	S/N Ratio	≥ 52 dB
	Backlight Compensation	Supported
	Visual Angel	H: 80°; V: 45°; D: 92°
	Auto White Balance	Supported
	Lens/Visual Angel	3.6mm lens
System Feature	Security	Account, Password user authentication, Reset button
	Image adjustment	Brightness, Contrast, Saturation, Sharpness adjustable
	Mobile Phone Monitor	Supports HD mobile phone monitoring via smart phone application for Android & iOS
	On-Board Storage	External TF card slot supports up to 128GB
	Digital Zoom	Supported
	Plug & Play	Adopting advanced Cloud-link P2P (Plug and play) technology, network penetration up to 99%, applicable to all kinds of complex networks
Audio	Audio Compression	AAC
	Audio Input	Built-in 36dB microphone
	Audio Output	Built-in speaker(8Ω1W)
PTZ Control	Pan & Tilt	Pan 0°~350°,Tilt 0°~100°
Video Management	Compression	H.264 Baseline profile
	Recording Mode	Continuous recording, Motion detection recording
	Video Storage	Support local storage TF card & network storage through LAN
Network	Ethernet	1 RJ45 10/100M self-adaptive Ethernet port
	Protocols	TCP/IP,HTTP,TCP,UDP/IP, DHCP,RTMP, MUDP, IPv4/IPv6
	Wireless	2.4G WIFI (IEEE802.11b/g/n), built-in 2DB antenna
Alarm	Alarm detection	Motion detection
	Alarm linkage	Snapshot, Audio/Video record
	Alarm notification	Real-time App push notifications
System Requirement	Mobile Client Application	Supported Software version IOS7.1, Android 4.0 and above
	LED Instruction	Network signal/Function indicator
Electrical	Power Supply	DC5V 2A
	Power consumption	<8W
Environmental	Enclosure	Indoor Pan-tilt Enclosure
	Operating Temperature	-10°C to + 60°C
	Operating Humidity	80% or less (non-condensing)
Mechanical	Color	White
	Dimensions	86(L)X86(W)x120(H)mm
	Weight	260g
Certification	Certification	CE, FCC, RoHS

VV-NC700P2P-F3



VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton
West Midlands, WV6 0JZ United Kingdom

Ph: +44-1902793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO 14001 : 2004 CERTIFIED COMPANY)

