




# HIGH PERFORMANCE

**H.265 NETWORK VIDEO RECORDER** 

### VV-NV3432-R8ST1

32 CHANNEL SMART NVR



## VV-NV3432-R8ST1

| System                         | Operating System                    | Embedded Linux Operating System   |
|--------------------------------|-------------------------------------|---|
|                                | Multiplex Operations                | Simultaneous multi-channel real-time recording, playback, network operation, USB backup     |
|                                | User interface                      | Support 16-bit true color graphical menu interface and mouse operation                      |
|                                | Bandwidth In/Out                    | 256Mbps/ 256Mbps  |
| Interface                      | IP Video Input                      | 32-ch   |
|                                | Two way Audio Input                 | 1-ch, RCA (2.0 Vp-p, 1kΩ)   |
|                                | VGA Video Output                    | 1-ch, Resolution: 1920×1080/1280×1024/1024×768  |
|                                | HDMI Video Output 1                 | Resolution: 4K x 2K /1920×1080/1280×1024/1024×768   |
|                                | HDMI Video Output 2                 | Resolution: 1920×1080/1280×1024/1024×768  |
|                                | Audio Output                        | 1-ch, RCA (2.0 Vp-p, 1kΩ)   |
|                                | Multi-screen Display                | 1/4/6/8/9/13/16/25/32/36  |
|                                | Alarm Input / Output                | 8/4   |
|                                | Network                             | 2 x Gigabit (10/100/1000) ethernet port   |
|                                | USB                                 | USB 3.0 x 1, x USB 2.0 x 2  |
| Resolution &<br>Frame Rate     | Recording Resolution                | 12MP/8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H<br>960P/720P/960H/D1/CIF            |
|                                | Frame Rate                          | Main stream: 25 fps (P) / 30 fps (N)<br>Sub stream: 25 fps (P) / 30 fps (N)                 |
|                                | Playback Resolution                 | 12MP/8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H<br>960P/720P/960H/D1/CIF            |
|                                | Max playback capability             | 16 ch playback  |
|                                | Compression                         | H.265+/ H.265/ H.264  |
|                                | DDNS                                | Supported; Dynamic and Static IP support  |
| Network & Remote<br>Monitoring | Protocol                            | TCP / IP,PPPoE, DHCP,DNS,DDNS, UPnP, NTP, SMTP, RTSP,HTTP, HTTPs, 802.1x, SNMP, ONVIF, etc. |
|                                | CMS                                 | Full function CMS (Central Monitoring Software)   |
|                                | Mobile Client<br>Application        | Supports android and iOS APP for Smart phone and tablets                                    |
|                                | Bandwidth control                   | CBR (Manual) supported  |
|                                | Security                            | Password protection, User management  |
| Features                       | Playback Function                   | Play/ Pause/ Fast forward/ Backward/ Digital zoom   |
|                                | Search Mode                         | Time/ Date/ Alarm/ Motion Detection/ Tag/ Event/ Smart Search                               |
|                                | Alarm Triggering                    | Record, Snapshot, Preset, Email   |
|                                | Channel                             | 32ch  |
|                                | Face Picture Database               | 32 libraries, 5000 Face Pictures  |
|                                | Computing Capability                | 180 pictures / minute   |
| Face                           | Face Picture Search                 | Search by picture is supported  |
|                                | Database<br>Management              | Add, modify, delete and search face pictures  |
|                                | Face Picture Adding                 | Add face pictures through APP, WEB and local PC   |
|                                | Face Picture<br>Comparison          | Support allow list, block list and stranger match alarm                                     |
|                                | Track                               | Track display on a map  |
|                                | Statistic Graph of Face Information | Bar graph, Pie chart  |
|                                | Statistic Mode of Face Information  | Statistics by day, week, month, quarter as well as customized time period                   |
| Video Analytics                | Smart Features                      | Object abandoned/missing, region intrusion, tripwire, video exception                       |
|                                |                                     |   |

#### **TECHNICAL SPECIFICATIONS**

### VV-NV3432-R8ST1

| Recording &<br>Storage | Recording Mode        | Manual/Alarm/Motion Detection/Continuous      |
|------------------------|-----------------------|---|
|                        | Storage               | 8 SATA port up to 10TB each                   |
|                        | e-Sata                | 2x e-Sata                                     |
|                        | RS 485                | Yes (full-duplex); connect to PTZ or keyboard |
|                        | Raid                  | RAIDO, RAID1, RAID5, RAID6, RAID10            |
| General                | Power Supply          | ATX 250W                                      |
|                        | Power Consumption     | <30W (Hard disk not included)                 |
|                        | Operating temperature | -10°C to + 50°C                               |
|                        | Working Humidity      | 90% or less (non condensing)                  |
|                        | Dimensions            | 445×436×90(W×D×H)                             |
|                        | Weight                | ≤4Kg ( without hard disk)                     |
| Certifications         | Certifications        | CE,FCC,RoHS                                   |

<sup>\*</sup>Actual product and specifications may differ from the images appearing in the brochure and are subject to change without notice due to ongoing product development.

#### **Dimension:**

Unit: mm





### **VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED**

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902-793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001: 2008, ISO 14001: 2004 CERTIFIED COMPANY)





