



HIGH PERFORMANCE

H.265 NETWORK VIDEO RECORDER

VV-NV3504-K1ST1

4 CHANNEL NVR



Al recording

Mobile Monitoring

Motion Detection

VV-NV3504-K1ST1

	Operating System	Embedded Linux Operating System
System	Multiplex Operations	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
	User interface	Support 16-bit true color graphical menu interface and mouse operation
Bandwidth	Incoming / Outgoing	80/80 Mbps
Interface	IP Video Input	4-ch
	VGA Video Output	1920×1080/1280×1024/1024× 768
	HDMI 1	3840 × 2160 / 1920 × 1080 / 1280 × 1024/ 1024 × 768
	Two-Way Audio	RCA × 1
	Alarm Input / Output	Supports IPC alarm input/output
	Network	1 x Gigabit (10/100/1000) ethernet port (RJ45)
	Audio Output	RCA x 1
	USB	USB 2.0 × 2
	Multi-screen Display	1/4
	Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H/D1/CIF
	Frame Rate	Main stream: 25 fps (P) / 30 fps (N) Sub stream: 25 fps(P) / 30 fps (N)
Resolution &	Playback Resolution	8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H/D1/CIF
Frame Rate	Max playback capability	Max 4ch playback
	Live View/ Playback	1CH 8MP/4CH 1080P
	Video Compression	H.265S / H.265+ /H.265 /H.264
Compression	Audio Compression	G.711(U/A)
	Protocols	TCP / IP, IPv4, IPv6, UDP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, HTTP, SMTP, HTTPS, 802.1x, RTSP, RTP, RTP, RTCP, FTP, WebSocket, SNMP, IGMP, ONVIF
	DDNS	Supported; Dynamic and Static IP with QR Code support
Network & Remote	CMS	Full function CMS (Central Monitoring Software)
Monitoring	Mobile Client Application	Supports android and iOS APP for Smart phone and tablets
	Bandwidth control	VBR/CBR
	Client Connection	Max. 64 users access
	Security	Password Protection, User Management
	Playback Function	Play, pause, FF, FB, digital zoom, etc
	Playback Search	Time slice / time / event / tag search
Features	Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
	Alarm Mode	Manual, sensor, motion, exception, smart events
	Alarm Triggering	Record, snap, preset, e-mail, etc.
	Alarm Notifications	FTP, SMTP, Email notification supported
Face Perimeter Protection	Face Detection Performance (AI by IPC)	4CH
	Face Detection Performance (Al by Device)	2 CH (2MP)
	Statistical Graph of Information	Bar graph
	Statistical Mode of Information	Statistics by day, week, month, quarter as well as customized time period
	Human/Vehicle Classification (AI by IPC)	4CH
	Human/Vehicle Classification (Al by Device)	2 CH(2MP)
Other Functions	Fisheye	Supports fisheye dewarping via Web Client and mobile APP
	Plate Detection (AI by IPC)	Yes, supported


VV-NV3504-K1ST1

Recording & Storage	Record Stream	Dual stream recording
	Storage	SATA 3.0x1, up to 10TB each
	Network Backup	Supported
	Local Backup	U disk, USB mobile HDD
General	Power Supply	DC 12V/1.5A
	Power Consumption	<105W (without HDD)
	Operating temperature	-10°C to + 50°C
	Working Humidity	90% or less (non condensing)
	Dimensions	300 × 249 × 45 (W × D × H)
Certifications	Certifications	CE, FCC, RoHS

^{*}Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image, weights and measurements are approximate and may vary.

Dimension

Unit: mm



B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902793383, Email: sales@vantagesecurity.com





(AN ISO 9001: 2008, ISO14001: 2004 CERTIFIED COMPANY)

