

ACCESS & TIME MANAGEMENT SYSTEM

VV-RF110S-FPCAS13

STANDALONE FINGERPRINT ACCESS CONTROLLER & WIEGAND READER



FEATURES

Wi-Fi based dual mode- standalone access control reader & entry & exit reader with Wiegand in/out

Manage device via mobile application, unlock & check door status remotely

Supports multiple verification modes- fingerprint/card/PIN

User Capacity of 200 fingerprints, 400 cards or PIN

Supports 125 KHz EM & Mifare 13.56 MHz

Supports anti tamper & anti-vandal function

Backlit touch keyboard function supported

Robust metal alloy outdoor enclosure with IP66 protection rating



Mobile App



Card



Access
Control



Touch
Keypad

TECHNICAL SPECIFICATIONS

VV-RF110S-FPCAS13

Users	Fingerprint 200 user Cards & Pin 400 user Visitors 10 user
Card Support	EM & Mifare
Card Reader	Supports EM 125KHz & Mifare 13.56MHz
Keypad	Touch Keypad
Wi-Fi	Supported
Read Range	<30mm
Relay	One(NO,NC,COM)
Adjustable Relay Output Time	0-99 Seconds(5 seconds default)
Wiegand Input & Output Format	26/34 bit
Operating Voltage	DC12V
Idle Current	<45mA
Active Current	<150mA
Operating Temperature	-20°C ~60°C
Operating Humidity	20~90% (non-condensing)
Ingress Protection Rating	IP66
Dimensions	130mm(L)x46mm(W)x16mm(H)
Weight	230g
Certification	CE,FCC,RoHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902-793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO 14001 : 2004 CERTIFIED COMPANY)

