

# ENTRANCE MANAGEMENT SYSTEM

## VV-VM7106EB-R/L6S4 Ultra Fast Electronic Boom Barrier



### FEATURES

High performance boom barrier with electro-mechanical motor

100% duty cycle with >1 million operations

Opening time & closing time adjustable 1.8s/3s/6 sec.

Traffic light can be integrated to further enhance safety


IP65 Ingress protection rating and hand crank for manual operations

Push button with up, down and stop functionality

Toll and high traffic application

Integration support with any RFID/biometric reader through no input

Straight boom up to 6 mtr length supported



## TECHNICAL SPECIFICATIONS

### VV-VM7106EB-R/L6S4

Parameter	Specifications
Drive	Turbine worm transmission Motor
Service Life	>1 million
Rod Type	Straight boom
Rod Lift Time	1.8s (3mtr) /3s (4 mtr) /6s (6 mtr)
Rod Length	3/4.5/6 meters
Maximum Remote Control Distance	≤15m
Motor Power Consumption	90W
Frequency	60HZ
Working Voltage	AC220 V
Operating Temp.	-30° to 80°
Barrier Dimension.	355x245x1035mm
Gross Weight	47 kg
Certifications	CE, FCC, ROHS

\*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image, weights and measurements are approximate and may vary.

## VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED.

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902-793383, Email: [sales@vantagesecurity.com](mailto:sales@vantagesecurity.com)

[www.vantagesecurity.com](http://www.vantagesecurity.com)

(AN ISO 9001 : 2008, ISO 14001 : 2004 CERTIFIED COMPANY)

