

VEHICLE ENTRANCE MANAGEMENT SYSTEMS

VV-VM7410FD-BLZ4

FIXED STAINLESS STEEL BOLLARD



FEATURES

Fixed bollard for high security and strong anti-collision strength

High grade reflector for long distance visible warning

IP68 ingress- protection rating

AISI 304 grade stainless steel construction

INGRESS
PROTECTION
RATING

IP68



100%
Duty Cycle

TECHNICAL SPECIFICATIONS

VV-VM7410FD-BLZ4

Physical Features & Characteristics	Type	Fixed
	Visible Warning Signage	High grade reflector tape at the brim
	Crash Resistance Design	Tested with vehicle of 7.5 ton weight moving at a speed of 48 Kmph
	Cylinder Diameter	273mm
	Cylinder Intercept Height	1200mm
	Cylinder Material	304 stainless steel
	Cylinder Thickness	40mm
	Bollard Underground Base Dimension	φ273mm x 400mm
	Base Flange Diameter	375mm
	Underground Base Material	High density Q235 Carbon steel
	Weight	Approx.120Kg
	Weather Protection	IP68 rated
Approvals	Certifications	CE,RoHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED.

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902-793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO9001 : 2008, ISO14001:2004 CERTIFIED COMPANY)

